

P24476

POWER SUPPLY SYSTEM

00015693 032304

## BACKGROUND OF THE INVENTION

### 1. FIELD OF THE INVENTION:

5       The current invention relates to a power supply system for supplying power stably while achieving energy savings in, for example, offices and homes.

### 2. DESCRIPTION OF THE RELATED ART:

10       Conventionally known environment-conscious power generation systems include solar energy power generation systems using solar cells and power generation systems using fuel cells.

15       The solar energy power generation systems are roughly classified into two, i.e., (i) an "independent system" and (ii) an "association system". In the "independent system", an electric energy generated by solar energy power generation is accumulated in a storage cell and then utilized. In the "association system", a solar cell  
20       is connected to an electric line of a power company via an inverter. When the amount of power generated by the solar energy generation exceeds the power consumption in a house (for example, daytime on a clear day), the excess amount of the power is purchased by the power company; and when  
25       the amount of power generated by the solar energy generation does not reach the power consumption in a house (for example, a rainy day or nighttime), the necessary power is purchased from the power company.

30       One known example of power generation systems using fuel cells is a home-use co-generation system (see Nikkei Electronics, No. 763, pp. 55-62). The co-generation system described in this document realizes power generation

using a fuel cell by providing a polymer-type fuel cell with fuel gas (for example, natural gas or LP gas). The electric energy thus generated is supplied to electric products in houses. The heat discharged from the fuel cell is used for  
5 hot water supply or room heating.

The solar cell power generation systems have a problem in terms of effective use of energy. In the "independent system", the generated electric energy is  
10 accumulated in a storage cell, and thus an energy loss occurs. In the "association system" also, an energy loss occurs while the excess amount of the power which is sold to the power company is transferred thereto through an electric line.

The co-generation system using a fuel cell is expected to be common in homes and offices. However, it has not been considered how to build a new power supply system appropriate to a fuel cell, specifically, how to stably  
15 supply power while achieving energy savings.

20

#### SUMMARY OF THE INVENTION

According to one aspect of the invention, a power supply system includes a plurality of electric products;  
25 a power generation apparatus capable of varying an amount of power generation; and a power control apparatus for controlling power supply from the power generation apparatus to the plurality of electric products. Each of the plurality of electric products is structured to be capable of  
30 outputting a first power request signal for requesting a desired amount of power. The power control apparatus receives the plurality of first power request signals respectively from the plurality of electric products.

0015503 03204  
102220 00551800

generates a second power request signal for  $r$  requesting an amount of power which is determined in accordance with a total amount of power requested by the plurality of first power request signals, and outputs the second power request signal to the power generation apparatus. The power generation apparatus increases or decreases the amount of power generation so as to match the amount of power generation with a target amount of power generation which is determined in accordance with the second power request signal.

In one embodiment of the invention, the power generation apparatus is a fuel cell.

In one embodiment of the invention, the power control apparatus generates the second power request signal so as to fulfill  $R = \sum R_i + R_m$ , where  $R$  indicates an amount of power requested by the second power request signal,  $R_i$  ( $i = 0, 1, \dots, n$ ) indicates an amount of power requested by each of the plurality of first power request signals, and  $R_m$  indicates a minimum necessary amount of power for communication between the plurality of electric products and the power control apparatus.

In one embodiment of the invention, the power generation apparatus determines whether or not the amount of power generation matches the target amount of power generation which is determined in accordance with the second power request signal; and when the amount of power generation is determined to match the target amount of power generation. The power generation apparatus outputs a matching signal to the power control apparatus. The power control apparatus outputs an acknowledging signal to each of at least one

electric product which outputs the first power request signal among the plurality of electric products, in response to the matching signal.

5           In one embodiment of the invention, the power generation apparatus determines whether or not the amount of power generation matches the target amount of power generation which is determined in accordance with the second power request signal. When the amount of power generation  
10 is determined to match the target amount of power generation, the power generation apparatus outputs an acknowledging signal to each of at least one electric product which outputs the first power request signal among the plurality of electric products.

15           In one embodiment of the invention, the power supply system further includes a power supply apparatus for outputting at least one of power supplied from the power generation apparatus and power supplied from a power supply  
20 source other than the power generation apparatus. The power generation apparatus determines whether or not the amount of power generation matches the target amount of power generation which is determined in accordance with the second power request signal. When the amount of power generation  
25 is determined to match the target amount of power generation, the power generation apparatus outputs a matching signal to the power control apparatus. The power control apparatus determines whether or not an amount of power requested by a current second power request signal is increased as  
30 compared with an amount of power requested by a previous second power request signal. When it is determined that the amount of power requested by the current second power request signal is increased as compared with the amount of power

001553 03301

requested by the previous second power request signal, the power control apparatus controls the power supply apparatus to compensate for an insufficiency in the power supplied from the power generation apparatus with power supplied from the power supply source, during a period from when the current second power request signal is output to the power generation apparatus until when the matching signal is received from the power generation apparatus.

In one embodiment of the invention, the power control apparatus controls the power supply apparatus to compensate for the insufficiency in the power supplied from the power generation apparatus with power supplied from the power supply source only when the increase of the amount of power requested by the current second power request signal over the amount of power requested by the previous second power request signal is equal to or more than a prescribed value.

In one embodiment of the invention, the power supply source supplies commercial power.

In one embodiment of the invention, the power supply source is a storage cell.

In one embodiment of the invention, the plurality of electric products are connected to the power control apparatus via a wireless system or a wired system.

In one embodiment of the invention, the first power request signal is a state signal indicating a state of the electric product, and the power control apparatus obtains an amount of power required by the electric product in the

state which is indicated by the state signal, and generates the second power request signal based on the amount of power required by the electric product.

5           According to another aspect of the invention, a computer system includes a server computer and a terminal. The server computer includes a storage section for storing a correspondence table indicating a relationship between a state of an electric product and power consumption of the  
10       electric product in the state. The correspondence table is downloaded from the server computer through a network in accordance with a request from the terminal.

15           In one embodiment of the invention, the terminal is connected to a power supply system. The power supply system includes a plurality of electric products, a power generation apparatus capable of varying an amount of power generation, and a power control apparatus for controlling power supply from the power generation apparatus to the  
20       plurality of electric products. The downloaded correspondence table is stored in the power control apparatus.

25           According to still another aspect of the invention, a method for selling an electric product includes the step of selling an electric product with a URL address for obtaining a correspondence table regarding the electric product, the correspondence table indicating a relationship between a state of the electric product and power consumption  
30       of the electric product in the state.

Thus, the invention described herein makes possible the advantages of providing a power generation system for

[illegible]

**5**

10

15

20

25

30

Figure 6 is a view illustrating a structure of a power supply system 3 in a third example according to the current invention:



5            Figure 8 is a diagram illustrating an internal structure of a power supply apparatus 200 in the power supply system 3 shown in Figure 3;

Figure 10 is a timing diagram illustrating waveforms of various signals used in the power supply system 3 shown in Figure 6;

Figure 12A shows an example of a correspondence table 510 on a TV having a BS recording function;

Figure 13A shows an example of a home page of a "web site for electric products usable for the power supply system";

Figure 13B shows an example of a "search for a correspondence table" web page; and

Figure 13C shows an example of a "confirm the correspondence table" web page.

#### DESCRIPTION OF THE EMBODIMENTS

5

Hereinafter, the current invention will be described by way of illustrative examples with reference to the accompanying drawings.

10 (Example 1)

Figure 1 shows a structure of a power supply system 1 in a first example according to the current invention. The power supply system 1 is an example of an independent type power supply system of generating all the power necessary in a house without being supplied with power from any other power supply source.

The power supply system 1 includes a plurality of electric products 40-1 through 40-n, a power generation apparatus 20 capable of varying an amount of power generation, and a power control apparatus 30 for controlling power supply from the power generation apparatus 20.

In the following description, the power generation apparatus 20 is assumed to be a fuel cell (for example, PEFC or polymer electrolyte fuel cell). The fuel cell is supplied with hydrogen produced from fuel gas such as municipal gas by a fuel quality improving apparatus (not shown). The reason why the power generation apparatus 20 is assumed to be a fuel cell is that a fuel cell is most practical as a power generation apparatus capable of varying an amount of power generation in today's state of the art. Any type of power generation apparatus capable of varying an amount of

00015603 032304  
T02220 032304

power generation can be used as the power generation apparatus 20.

Each of the plurality of electric products 40-1 through 40-n can be any product such as, for example, a refrigerator, a television (TV), a lighting device, a personal computer (PC), a microwave oven, an audio player, a DVD player, a telephone, or a fax. In the following description, it is assumed that the electric product 40-1 is a refrigerator, the electric product 40-2 is a TV, the electric product 40-(n-1) is a lighting device, and the electric product 40-n is a personal computer, as shown in Figure 1.

The plurality of electric products 40-1 through 40-n are each connected to the power control apparatus 30 via a dedicated line. However, the connection between the plurality of electric products 40-1 through 40-n and the power control apparatus 30 is not limited to this. For example, the plurality of electric products 40-1 through 40-n can be connected to the power control apparatus 30 via a wireless or wired system. As a wireless system, for example, Blue Tooth or a communication line for cellular phones or PHS is usable. As a wired system, for example, a telephone line such as ISDN or a local area network (LAN) such as HAVI or Eiconet is usable.

The power generated by the fuel cell 20 is supplied to the plurality of electric products 40-1 through 40-n via an inverter 10. The inverter 10 converts DC power into AC power. It is assumed that the plurality of electric products 40-1 through 40-n are continuously supplied with a minimum required amount  $R_m$  of power for communication between the

plurality of electric products 40-1 through 40-n and the power control apparatus 30. Herein, the "minimum required amount  $R_m$  of power for communication between the plurality of electric products 40-1 through 40-n and the power control apparatus 30" includes the power required to transfer data between the plurality of electric products 40-1 through 40-n and the power control apparatus 30 and the power consumed by the plurality of electric products 40-1 through 40-n while they are at wait.

The electric product 40-1 is structured to output a power request signal  $R_i$  (first power request signal) for requesting a desired amount of power to the power control apparatus 30. Here,  $i = 1, \dots, n$ .

For example, it is assumed that when a power switch of the electric product 40-1 (refrigerator) is switched from off to on, an amount of power which is necessary for the electric product 40-1 to perform a rated operation is  $p_1$  (W). In this case, when the power switch of the electric product 40-1 is switched from off to on, the electric product 40-1, in response to the switching, outputs a power request signal  $R_i$  for requesting the amount  $p_1$  of power which is necessary to perform the rated operation.

The power control apparatus 30 receives a plurality of power request signals  $R_i$  from the respective plurality of electric products 40-1 through 40-n. The power control apparatus 30 generates a power request signal  $R$  (second power request signal) for requesting an amount of power which is determined in accordance with a total amount of power requested by the plurality of power request signals  $R_i$ , and outputs the power request signal  $R$  to the fuel cell 20.

**5**

**15**

30

In step ST1, the power control apparatus 30 receives power request signal  $R_i$  from the electric product 40-1 which outputs the power request signal  $R_i$  among the plurality of electric products 40-1 through 40-n. The power request signal  $R_i$  is sent to the power control apparatus 30 from the electric product 40-1. The power request signal  $R_i$  indicates the number of watts ( $p_i$ ) of power necessary to put the electric product 40-1 into a usable state. Here, in a power request signal  $R_i$  indicating a "request for use",  $p_i > 0$ . In a power request signal  $R_i$  indicating a "request for non-use",  $p_i = 0$ . A power request signal  $R_i$  is represented by, for example, 8-bit digital data.

The power request signal  $R_i$  is held in the power control apparatus 30 until the next power request signal  $R_i$  is received by the power control apparatus 30.

In step ST2, the power control apparatus 30 generates a power request signal  $R$  so as to fulfill expression (1). The power request signal  $R$  indicates the number of watts ( $p$ ) of power to be supplied by the fuel cell 20. The power request signal  $R$  is represented by, for example, digital data having a prescribed number of bits.

$$R = \sum_{i=1}^n R_i + R_m \quad \text{..... expression (1)}$$

Here,  $R_i$  ( $i = 1, \dots, n$ ) indicates the amount of power requested by the power request signal  $R_i$ .  $R_m$  indicates the minimum necessary amount of power for communication between the plurality of electric products 40-1 through 40-n and the power control apparatus 30.

In step ST3, the power control apparatus 30 outputs the power request signal R to the fuel cell 20, thereby instructing the fuel cell 20 to perform power generation in accordance with the power request signal R.

5

The fuel cell 20 receives the power request signal R from the power control apparatus 30 and controls the amount of power generation so as to match the amount of power generation with a target amount of power generation which is determined in accordance with the power request signal R. The target amount of power generation of the fuel cell 20 can be set to be matched to the amount of power requested by the power request signal R or can be set to be matched to a sum of the amount of power requested by the power request signal R and a margin m in consideration of the margin m. The amount of power generation of the fuel cell 20 is increased or decreased by, for example, increasing or decreasing the supply amount of fuel gas such as natural gas or LP gas. Alternatively, when the fuel quality improving apparatus is not necessary, hydrogen can directly be supplied to the fuel cell 20.

The fuel cell 20 determines whether or not the amount of power generation matches the target amount of power generation which is determined in accordance with the power request signal R. When the amount of power generation is determined to have matched, the fuel cell 20 outputs a matching signal C to the power control apparatus 30.

In step ST4, the power control apparatus 30 confirms whether or not the matching signal C is received from the fuel cell 20.

1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------

20        To the electric product 40-1 which has output a power  
request signal R1 indicating a "request for non-use", the  
power control apparatus 30 does not return an acknowledging  
signal. The "request for non-use" is a request for reducing  
the amount of power requested. Accordingly, it is not  
necessary to inform the electric product 40-1 which outputs  
a power request signal Ri indicating a "request for non-use"  
that "the amount of power generation of the fuel cell 20  
25        has reached the target amount of power generation. The  
electric product 40-1 which outputs a power request signal  
Ri indicating a "request for non-use" starts an operation  
corresponding to the "request for non-use" immediately after  
outputting such a power request signal Ri to the power  
30        control apparatus 30 without waiting for receipt of the  
acknowledging signal from the power control apparatus 30.  
Here, an operation corresponding to the "request for  
non-use" encompasses "no operation".



When the electric product 40-1 is connected to the power control apparatus 30 via a dedicated line, the acknowledging signal is sent by, for example, changing the level of a power permission signal A1 (which is continuously output from the power control apparatus 30 to the electric product 40-1) from a low level (0) to a high level (1). Here, the high level (1) of the power permission signal A1 means that a power supply to the electric product 40-1 is permitted, and the low level (0) of the power permission signal A1 means that a power supply to the electric product 40-1 is not permitted (i.e., the power supply is prohibited).

When the electric product 40-1 is connected to the power control apparatus 30 through a local area network (LAN), the power permission signal A1 does not need to be continuously output to the electric product 40-1. In this case, the power control apparatus 30 can be structured to send the power permission signal A1 to the electric product 40-1 in response to an occurrence of an event (for example, the user's operation of the power switch from off to on).

At the time when the electric product 40-1 outputs a power request signal R1 indicating a "request for use" to the power control apparatus 30, the level of the power permission signal A1 supplied to the electric product 40-1 is set to be a low level (0). The power control apparatus 30 changes the level of the power permission signal A1 from a low level (0) to a high level (1) after confirming that the matching signal C is received from the fuel cell 20. This means that at the time when the amount of power generation of the fuel cell 20 reaches the target amount of power generation, the level of the power permission signal

5

15

30

[illegible]

and then starts an operation corresponding to the "request for use". This guarantees that electric product 40-1 operates under conditions which are necessary for the electric product 40-1 to realize a prescribed function without fail (rated conditions); namely, this guarantees that the electric product 40-1 performs a rated operation. As a result, the frequency of the electric product 40-1 malfunctioning is significantly reduced.

Also according to the above-described power supply system 1, the electric product 40-1 which outputs a power request signal R<sub>i</sub> indicating a "request for non-use" immediately starts an operation corresponding to the "request for non-use" without confirming that "the amount of power generation of the fuel cell 20 has reached the target amount of power generation". This allows the electric product 40-1 to be put into a non-use state rapidly when the user demands to put the electric product 40-1 into a non-use state (for example, when the user demands to stop the operation of the electric product 40-1).

In the first example, the fuel cell 20 determines whether or not the amount of power generation has reached the target amount of power generation which is determined in accordance with a power request signal R. Then, the fuel cell 20 outputs a matching signal C indicating the result of the determination to the power control apparatus 30. In response to the matching signal C, the power control apparatus 30 outputs an acknowledging signal to each of at least one electric product 40-1 which outputs a power request signal R<sub>i</sub> indicating a "request for use". Alternatively, the fuel cell 20 can directly return the acknowledging signal to each of at least one electric product 40-1 which outputs

2025-03-04 10:00:00

a power request signal R<sub>1</sub> indicating a "request for use". In order to realize this, however, the power control apparatus 30 needs to be structured to output a power request signal R<sub>1</sub> to the fuel cell 20 as well as a power request signal R.

(Example 2)

Figure 3 shows a structure of a power supply system 2 in a second example according to the current invention. The power supply system 2 is an example of a type of power supply system which, in principle, generates all the power necessary in a house using a fuel cell, but when the amount of power generation is insufficient, receives power (for example, commercial power) from a power supply source other than the fuel cell until the amount of power generation is confirmed to reach the target amount of power generation.

In Figure 3, identical elements previously discussed with respect to Figure 1 bear identical reference numerals and the detailed descriptions thereof will be omitted.

The power supply system 2 includes a power supply apparatus 100 in addition to the elements in the power supply system 1 (Figure 1).

The power supply apparatus 100 outputs at least one of power supplied from the fuel cell 20 and power supplied from a power company 80 via a power line 90 to each of the plurality of electric products 40-1 through 40-n.

A power control apparatus 300 includes a buffer (not shown) for storing a power request signal R which was output

1. The first part of the report is a general statement of the purpose of the study.

As described above, the power control apparatus 300 controls the power supply apparatus 100 to compensate for the insufficiency in the amount of power supplied from the fuel cell 20 with the power supplied from the power company 80 via the power line 90 until the amount of power generation of the fuel cell 20 is confirmed to reach the target amount

of power generation (i.e., the period from the output of the current power request signal R to the fuel cell 20 until the receipt of the matching signal C from the fuel cell 20). Thus, the power control apparatus 300 can return an  
5 acknowledging signal at real time to the electric product 40-1 which outputs a power request signal Ri indicating a "request for use" without waiting until the amount of power generation of the fuel cell 20 reaches the target amount of power generation. As a result, the user is prevented from  
10 experiencing the discomfort of delayed start of the operation of the electric product 40-1.

The power control apparatus 300 can alternatively be structured to determine whether or not the increase of  
15 the amount of power generation requested by the current power request signal R over the amount of power generation requested by the previous power request signal R is equal to or more than a prescribed value. In this case, the power control apparatus 300 can be structured to control the power  
20 supply apparatus 100, only when the excess is determined to be equal to or more than the prescribed value, to compensate for the insufficiency in the power supplied by the fuel cell 20 with the power supplied via the power line 90 until the amount of power generation of the fuel cell  
25 20 is confirmed to reach the target amount of power generation.

The power supply source other than the fuel cell 20 which is connected to the power supply apparatus 100 can  
30 be any type of power supply source. The power supply source can be, for example, a commercial power supply source or a storage cell.

Figure 4 shows a procedure of processing executed by the power control apparatus 300. In the example shown in Figure 4, it is assumed that a power request signal R<sub>i</sub> output from the electric product 40-1 indicates a "request for use" or a "request for non-use".

In step ST1, the power control apparatus 300 receives a power request signal R<sub>i</sub> from the electric product 40-1 which outputs the power request signal R<sub>i</sub> among the plurality of electric products 40-1 through 40-n. The processing in step ST1 is the same as that shown in Figure 2.

In step ST2, the power control apparatus 300 generates a power request signal R so as to fulfill expression (1). The processing in step ST2 is the same as that shown in Figure 2.

In step ST3, the power control apparatus 300 outputs the power request signal R to the fuel cell 20, thereby instructing the fuel cell 20 to perform power generation in accordance with the power request signal R. The processing in step ST3 is the same as that shown in Figure 2.

In step ST4, the power control apparatus 300 determines whether or not the amount of power generation requested by the "current power request signal R" is increased as compared with the amount of power generation requested by the "previous power request signal R". When it is determined that the amount of power generation requested by the "current power request signal R" is increased as compared with the amount of power generation

requested by the "previous power request signal R", the power control apparatus 300 outputs a power purchase signal T to the power supply apparatus 100, thereby instructing the power supply apparatus 100 to purchase an amount of power corresponding to the insufficiency in the power generated by the fuel cell 20 from the power company 80.

In step ST5, to the electric product 40-1 which has output a power request signal Ri indicating a "request for use", the power control apparatus 300 returns an acknowledging signal without confirming receipt of a matching signal C from the fuel cell 20. The power control apparatus 300 can send the acknowledging signal in this manner by immediately changing the level of the power permission signal Ai from a low level (0) to a high level (1) when the power request signal Ri indicating a "request for use" is received from the electric product 40-1 without waiting for the receipt of the matching signal C from the fuel cell 20.

To the electric product 40-1 which has output a power request signal Ri indicating a "request for non-use", the power control apparatus 300 does not return an acknowledging signal. The processing in this case is the same as that in step ST4 in Figure 2.

In step ST6, the power control apparatus 300 confirms whether or not a matching signal C is received from the fuel cell 20. Upon confirming receipt of the matching signal C is received from the fuel cell 20, the power control apparatus 300 outputs a power purchase signal T to the power supply apparatus 100, thereby instructing the power supply apparatus 100 to stop the purchase of the power supplied



from the power company 80.

Figure 5 shows an internal structure of the power supply apparatus 100. The power supply apparatus 100 includes a power purchase device 100a and a power adder 100b.

The power purchase device 100a is connected to the power company 80 (Figure 3) via the power line 90. In accordance with the value of the power purchase signal T, the power purchase device 100a switches the power from the power company 80 to be permitted to be supplied to the power adder 100b or prohibited from being supplied to the power adder 100b. The power purchase device 100a includes, for example, a switch (not shown) for determining whether the power adder 100b should be electrically connected to the power company 80 or not. The switch is opened or closed in accordance with the value of the power purchase signal T.

The power adder 100b is connected between an output of the power purchase device 100a and an output of the inverter 10. The power adder 100b adds an output from the power purchase device 100a and an output from the inverter 10 and outputs the sum result to the plurality of electric products 40-1 through 40-n.

According to the power supply apparatus 100 having a structure shown in Figure 5, when the power purchase signal T permits the power from the power company 80 to be supplied to the power adder 100b, an amount of power corresponding to the insufficiency in the power generated by the fuel cell 20 is pulled into the power adder 100b from the power company 80 via the power purchase device 100a. As a result, even until the amount of power generation of the fuel cell 20

2025012351550

reaches the target amount of power generation, an appropriate amount of power is output from the power adder 100b.

5           According to the power supply system 2, as described  
above, the power control apparatus 300 immediately returns  
an acknowledging signal to the electric product 40-1 which  
10           outputs a power request signal Ri indicating a "request for  
use" upon receiving such a power request signal. This is  
permitted since even until the amount of power generation  
of the fuel cell 20 reaches the target amount of power  
15           generation, stable supply of power to the electric product  
40-1 is guaranteed. Therefore, it is not necessary for the  
electric product 40-1 which outputs the above-mentioned  
power request signal Ri to wait to start an operation  
20           corresponding to the "request for use" until the amount of  
power generation of the fuel cell 20 reaches the target  
amount of power generation. As a result, the electric  
product 40-1 can immediately start an operation  
25           corresponding to the "request for use" after outputting the  
above-mentioned power request signal Ri to the power control  
apparatus 300. This guarantees that the electric product  
40-1 operates under rated conditions immediately after the  
electric product 40-1 outputs the power request signal Ri  
30           indicating a "request for use" to the power control apparatus  
300. As a result, the frequency of the electric product 40-1  
malfunctioning is significantly reduced.

30           Alternatively, the power control apparatus 300 can  
be structured not to return an acknowledging signal to the  
electric product 40-1 which outputs a power request signal  
Ri regardless of the type of the power request signal Ri  
received from the electric product 40-1 (for example,

regardless of whether the power request signal R1 indicates a "request for use" or a "request for non-use"). This is permitted since stable supply of power to the electric product 40-1 is guaranteed even until the amount of power generation of the fuel cell 20 reaches the target amount of power generation. Therefore, the electric product 40-1 can immediately start a desired operation after outputting a power request signal R1 to the power control apparatus 300 regardless of the type of the power request signal R1 output to the power control apparatus 300 (for example, regardless of whether the power request signal R1 indicates a "request for use" or a "request for non-use").

(Example 3)

Figure 6 shows a structure of a power supply system 3 in a third example according to the current invention. The power supply system 3 is an example of an integrated type power supply system which uses both a solar cell and a fuel cell. The power supply systems described in the first and second examples do not use a solar cell, but can use a solar cell together with a fuel cell.

The power supply system 3 generates all the power necessary in a house using a solar cell and a fuel cell in principle. However, the power supply system 3 is structured as follows: when the total amount of power generated by the solar cell and the fuel cell is insufficient, the power supply system 3 can purchase power (for example, commercial power) from a power supply source other than the solar cell or the fuel cell until the amount of power generation of the fuel cell is confirmed to reach a target amount of power generation; and when the total amount of power generated by the solar cell and the fuel cell is excessive, the power

supply system 3 can sell the excess amount of the power to a power company.

5 In Figure 6, the identical elements previously discussed with respect to Figure 1 bear identical reference numerals and the detailed descriptions thereof will be omitted.

10 The power supply system 3 includes a solar cell 110, an inverter 120 and a power supply apparatus 200 in addition to the elements in the power supply system 1 (Figure 1).

15 The solar cell 110 supplies power generated by solar energy to the power supply apparatus 200 through the inverter 120. The inverter 120 converts DC power to AC power.

20 The solar cell 110 outputs a power generation signal G, which indicates an amount of power generation of the solar cell 110, to a power control apparatus 310.

The power supply apparatus 200 is connected to a power company 80, homes 81a, 81b and a factory 82 via a power line 90. The power supply system 3 is located within a home 81.

25 The power supply apparatus 200 outputs a portion P3 of power P1 supplied from the solar cell 110 to a power company 80 via a power line 90. The power supply apparatus 200 also outputs an amount of power which is equal to a sum of (i) a remaining portion (P1-P3) of the power P1 supplied from the  
30 power company 80, (ii) power P2 supplied from the fuel cell 20, and (iii) power P4 supplied from the power company 80 via the power line 90 (namely,  $P1 + P2 - P3 + P4$ ) to the plurality of electric products 40-1 through 40-n.

5 The plurality of electric products 40-1 through 40-n  
and the solar cell 110 are each connected to the power control  
apparatus 310 via a dedicated line. However, the connection  
between the plurality of electric products 40-1 through 40-n  
and the solar cell 110 with the power control apparatus 310  
is not limited to this. For example, the plurality of  
electric products 40-1 through 40-n and the solar cell 110  
can each be connected to the power control apparatus 310  
10 via a wireless or wired system. As a wireless system, for  
example, Blue Tooth or a communication line for cellular  
phones or PHS is usable. As a wired system, for example,  
a telephone line such as ISDN or a local area network such  
as HAVI or Eiconet is usable.

15  
Figure 7 shows a procedure of processing executed  
by the power control apparatus 310. In the example shown  
in Figure 7, it is assumed that a power request signal Ri  
output from the electric product 40-1 indicates a "request  
20 for use" or a "request for non-use".

In step ST1, the power control apparatus 310  
receives a power request signal Ri from the electric product  
40-1 which outputs the power request signal Ri among the  
25 plurality of electric products 40-1 through 40-n. The power  
control apparatus 310 also receives a power generation  
signal G from the solar cell 110. The power generation  
signal G is represented by, for example, 8-bit digital data.

30 In step ST2, the power control apparatus 310  
generates a power request signal R so as to fulfill  
expression (2). The power request signal R indicates the  
number of watts (p) of the power to be supplied by the fuel

40015603-022304

cell 20. The power request signal R is represented by, for example, digital data having a prescribed number of bits.

$$R = \sum_{i=1}^n Ri + Rm - G \quad \text{..... expression (2)}$$

5                    Here, Ri (i = 1, ..., n) indicates the amount of power requested by the power request signal Ri. Rm indicates the minimum necessary amount of power for communication between the plurality of electric products 40-1 through 40-n and the power control apparatus 310. G indicates an amount of  
10 power generated by the solar cell 110.

                  In step ST3, the power control apparatus 310 determines whether the value of the power request signal R is positive or negative, and outputs a sign signal S  
15 indicating the determination result to the fuel cell 20 and the power supply apparatus 200. For example, the value of "1" of the sign signal S means that the value of the power request signal R is negative, and the value of "0" of the sign signal S means that the value of the power request signal  
20 R is 0 or positive.

                  When  $R \geq 0$  in step ST3, the processing goes to step ST4. When  $R < 0$  in step ST3, the processing goes to step ST8.  
25

                  The processing in steps ST4 through ST7 (processing performed when the amount of power generation of the fuel cell 20 is insufficient) is the same as the processing in steps ST3 through ST6 shown in Figure 4.  
30

                  In step ST8, the power control apparatus 310

5

10

15

20

**30**

[illegible]

request signal R and a sign signal S which indicates whether the value of the power request signal R is positive or negative.

5           When the sign signal S is determined to be 0 (i.e., the power request signal R is 0 or positive), the power distributor 200c outputs all the power P1 supplied from the solar cell 110 to the power adder 200b (i.e.,  $P3 = 0$ ).

10           When the sign signal S is determined to be 1 (i.e., the power request signal R is negative), the power distributor 200c outputs an excess amount of power  $|R|$  (=  $P3$ ) out of the power P1 supplied from the solar cell 110 to the power company 80 via the power line 90, and outputs the remaining power ( $P1 - P3$ ) to the power adder 200b.

15           The power adder 200b is connected to an output of the power purchase device 200a, to an output of the inverter 10, and to an output of the power distributor 200c. The power adder 200b adds an output P4 from the power purchase device 200a, an output P2 from the inverter 10, and an output ( $P1 - P3$ ) from the power distributor 200c, and outputs the sum result ( $P1 + P2 - P3 + P4$ ) to the plurality of electric products 40-1 through 40-n. Here, when  $R \geq 0$ ,  $P3 = 0$ , and when  $R < 0$ ,  $P3 = |R|$ .

20           Figure 9 shows an internal structure of the power control apparatus 310. The power control apparatus 310 includes n buffers 320-1 through 320-n, n logic OR devices 330-1 through 330-n, and a calculation device 360.

30           A plurality of power request signals R1-through Rn respectively output from the plurality of electric products

2025 RELEASE UNDER E.O. 14176



40-1 through 40-n are respectively stored in the buffers 320-1 through 320-n. In the example shown in Figure 9, each of the plurality of power request signals R1 through Rn is represented by 8-bit digital data. Here, the power request signal R1 indicates the number of watts which is required to use the electric product 40-1. In the power request signal R1 indicating a "request for use",  $p1 > 0$ ; and in the power request signal R1 indicating a "request for non-use",  $p1 = 0$ .

The electric product 40-1 which outputs a power request signal R1 indicating a "request for non-use" is in a wait state, and thus consumes an amount of power required in the wait state of the electric product 40-1. Signal Rm, which indicates a minimum necessary amount of power for communication between the plurality of electric products 40-1 through 40-n and the power control apparatus 310 is represented by, for example, 4-bit digital data. (Hereinafter, signal Rm will be referred to as the "minimum power signal Rm".) The minimum power signal Rm is preset to have a prescribed value. The minimum power signal Rm is input to the power control apparatus 310 beforehand. The electric product 40-1 requests the power control apparatus 310 to provide the "amount of power required in the wait state of the electric product 40-1" as a part of the amount of minimum power indicated by the minimum power signal Rm. Accordingly, the electric product 40-1 does not need to request the power control apparatus 310 for the "amount of power required in the wait state of the electric product 40-1" separately from the minimum power signal Rm. This is why  $p1 = 0$  in the power request signal R1 indicating a "request for non-use".

It is assumed that a power request signal  $R_1$ , once stored in any of the buffers 320-1 through 320-n, is not updated until the next power request signal  $R_1$  (output from the same electric product as the power request signal  $R_1$  stored in the buffer) is received by the power control apparatus 310.

The calculation device 360 receives a plurality of power request signals  $R_1$  through  $R_n$ , a minimum power signal  $R_m$  and a power generation signal  $G$ , and generates a power request signal  $R$  in accordance with expression (2).

The calculation device 360 also generates a sign signal  $S$  indicating the sign of the power request signal  $R$ .

In synchronization with the timing at which the power request signal  $R$  is output to the fuel cell 20, the calculation device 360 sets a power purchase signal  $T$  to a first level (for example, a high level) indicating a purchase of power from the power company 80 is permitted. In synchronization with the timing at which a matching signal  $C$  is received from the fuel cell 20, the calculation device 360 sets a power purchase signal  $T$  to a second level (for example, a low level) indicating the purchase of power from the power company 80 is to be stopped.

Each of a plurality of power permission signals  $A_1$  through  $A_n$  is generated based on an output from a corresponding one of the logic OR devices 330-1 through 330-n.

The internal structure of the power control

apparatus 300 (Figure 3) is the same as that of the internal structure of the power control apparatus 310 shown in Figure 9 except that a power generation signal G is not input to and a sign signal S is not output from the power control apparatus 300. In the power control apparatus 300, the calculation device 360 receives a plurality of power request signals R1 through Rn and a minimum power signal Rm, and generates a power request signal R in accordance with expression (1).

Figure 10 is a timing diagram illustrating waveforms of various signals used in the power supply apparatus 3 (Figure 6) in the third example. In Figure 10, R1 indicates a power request signal which is output from the refrigerator 40-1. R2 indicates a power request signal which is output from the TV 40-2. It is assumed that power generation by the solar cell 110 is performed. Accordingly, as shown in Figure 10, the power generation signal G has a positive value.

It is assumed that at time t1, the user wants to watch the TV 40-2 and operates the switch of the TV 40-2 from off to on. In this case, the TV 40-2 outputs a power request signal R2 indicating a "request for use" (in the example shown in Figure 10, a high level signal) to the power control apparatus 310. The power control apparatus 310 receives the power request signals R1 and R2 and minimum power signal Rm (not shown in Figure 10, see Figure 9) and the power generation signal G, and generates a power request signal R at time t1 in accordance with expression (2). The power control apparatus 310 determines the sign of the value of the power request signal R at time t1. In the example shown in Figure 10,  $R \geq 0$  at time t1. Accordingly, the power

control apparatus 310 instructs the solar cell 20 to generate power of the amount  $|R|$  corresponding to the insufficiency, and sets the power purchase signal T to a first level (for example, a high level) indicating a purchase of power from the power company 80 is permitted. The power control apparatus 310 changes the level of a power permission signal A2 from a low level to a high level substantially simultaneously when the power request signal R2 indicating a "request for use" is received from the TV 40-2. Then, in synchronization with the receipt of a matching signal C from the fuel cell 20, the power control apparatus 310 sets the power purchase signal T to a second level (for example, a low level) indicating the purchase of the power from the power company 80 is to be stopped (during a period from time t1 to time t2).

It is assumed that at time t2, the user wants to turn off the TV 40-2 and operates the switch of the TV 40-2 from on to off. In this case, the TV 40-2 outputs a power request signal R2 indicating a "request for non-use" (in the example shown in Figure 10, a low level signal) to the power control apparatus 310. The power control apparatus 310 receives the power request signals R1 and R2 and minimum power signal Rm (not shown in Figure 10, see Figure 9) and the power generation signal G, and generates a power request signal R at time t2 in accordance with expression (2). The power control apparatus 310 determines the sign of the value of the power request signal R at time t2. In the example shown in Figure 10,  $R < 0$  at time t2. Accordingly, the power control apparatus 310 cancels the instruction to the solar cell 20 to generate the power, and instructs the power supply apparatus 200 to sell the excess amount of power  $|R|$  to the power company 80. The power control apparatus 310 changes

the level of the power permission signal A2 from a high level to a low level substantially simultaneously when the power request signal R2 indicating a "request for non-use" is received from the TV 40-2.

5

In this manner, the power generation of the fuel cell 20 can be controlled in accordance with whether the power supply of the TV 40-2 is on or off.

10

As described above, the solar cell 110 and the fuel cell 20 are used in combination. Thus, when an amount of power generation of the fuel cell 20 is insufficient ( $R \geq 0$ ), power supplied from the power company 80 can be purchased; and when an amount of power generation of the solar cell 110 is excessive ( $R < 0$ ), the excess amount of the power can be sold to the power company 80.

15

In the power supply system 3, when an amount of power generation of the solar cell 110 is excessive ( $R < 0$ ), the excessive amount of the power can be stored in a storage cell (not shown) instead of being sold to the power company 80. In this case, when an amount of power generation of the fuel cell 20 becomes insufficient, the power stored in the storage cell can be used. Alternatively, when an amount of power generation of the fuel cell 20 becomes insufficient, generation of power of an amount corresponding to the insufficiency can be instructed to the fuel cell 20, and also the power stored in the storage cell can be used until the amount of power generation of the fuel cell 20 reaches the target amount of power generation.

20

25

30

In the power supply system 3, the power control apparatus 310 immediately returns an acknowledging signal

2025 RELEASE UNDER E.O. 14176

to an electric product 40-1 which outputs a power request signal R1 indicating a "request for use" upon receiving the power request signal R1 indicating a "request for use" from the electric product 40-1, without confirming receipt of a matching signal C from the fuel cell 20. By this system, the effect provided by the power supply system 2 is also provided by the power supply system 3.

Alternatively, in the power supply system 3, the power control apparatus 310 can be structured not to return an acknowledging signal to the electric product 40-1 which outputs a power request signal R1 regardless of the type of the power request signal R1 (for example, regardless of whether the power request signal R1 indicates a "request for use" or a "request for non-use"). By this system, the effect provided by the power supply system 2 is also provided by the power supply system 3.

In the first through third examples, the amount of power generated by the fuel cell 20 is controlled in accordance with the increase or decrease in the amount of power requested by the request signal R1 from the electric product 40-1. Instead, the amount of power generated by the fuel cell 20 can be controlled in accordance with a request based on the power consumption of the electric products 40-1, without a power request signal R1 being output from the electric products 40-1. For example, in a structure using the "association system", the amount of power generation of the fuel cell 20 can be changed by a result of monitoring a purchase of commercial power from the power company 80 conducted by the insufficiency of the power generated by the fuel cell 20. This system is usable since the result of monitoring shows the request based on the power

001553 03341  
TUEDEC 03 1994

1923	1924	1925	1926	1927	1928	1929	1930	1931	1932	1933	1934	1935	1936	1937	1938	1939	1940	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------

In the first through third examples, a power request signal Ri indicates a "request for use" or a "request for non-use". A power request signal Ri can indicate one of three or more requests. For example, a power request signal Ri can indicate a "request for high output use", a "request for low output use" or a "request for non-use". A power request signal Ri indicating a "request for high output use", for example, can request the power of 100 W. A power request signal Ri indicating a "request for low output use", for example, can request the power of 50 W. A power request

[illegible]

25

When the request is switched from a "request for high output use" to a "request for non-use" or when the request is switched from a "request for low output use" to a "request for non-use", the power control apparatus 30 (or 300 or 310) can change the level of a power permission signal Ai from a high level (1) to a low level (0) without confirming receipt of a matching signal C. When the request is switched from a "request for high output use" to a "request for low output



use", the power control apparatus 30 (or 300 or 310) can maintain the high level (1) without confirming receipt of a matching signal C.

5           In the first through third examples, a power request signal R1 indicates the number of watts of the power required to use the electric product 40-1. Instead, a power request  
10           signal R1 can indicate a state of the electric product 40-1 (power state). In this case, the power control apparatus 30 (or 300 or 310) can receive a state signal indicating a state of the electric product 40-1, as a power request  
15           signal R1, from the electric product 40-1, and obtain an amount of power required to use the electric product 40-1 in the state indicated by the state signal. For example, the power control apparatus 30 (or 300 or 310) can store, in an internal memory (not shown) thereof, a correspondence  
20           table which shows the relationship between the state signal and the amount of power required to use the electric product 40-1 in the state indicated by the state signal (for example, a look-up table). In this case, the correspondence table  
25           is used to convert a state signal into an amount of power required to use the electric product 40-1 in the state indicated by the state signal. Such a correspondence table is preferably prepared for each type or each system of electric products.

(Example 4)

30           Figure 11 shows a structure of a computer system 4 in a fourth example according to the current invention. The computer system 4 includes a server computer 410 and at least one terminal 420. The server computer 410 is connected to the at least one terminal 420 through the internet 430.

The server computer 410 includes a storage section 450 for storing at least one web page. The storage section 450 is, for example, a hard disk.

5           Figures 12A and 12B each show a correspondence table indicating the relationship between the state of an electric product and the power consumption of the electric product in that state, as an example of the content of the web page stored in the storage section 450 of the server computer 10           410. Figure 12A shows a correspondence table 510 for a TV having a BS recording function, and Figure 12B shows a correspondence table 520 for a washing machine. Each of the correspondence tables 510 and 520 is, for example, a look-up table.

15           The correspondence table 510 in Figure 12A shows that the TV having a BS recording function can be in one of three states (power states) of "on state", "off state" and "BS recording state". The correspondence table 510 also 20           shows that the power consumption for the "on state" is 220 W, the power consumption for the "off state" is 0 W, and the power consumption for the "BS recording state" is 18 W. The correspondence table 510 further shows that the three states are respectively indicated by three state signals S1, S2 25           and S3. The state signals S1, S2 and S3 are each represented by, for example, 2-bit digital data.

          The correspondence table 520 in Figure 12B shows that the washing machine can be in one of three states (power 30           states) of "washing by a centrifugal force", "washing by stirring" and "off state". The correspondence table 520 also shows that the power consumption for the "washing by a centrifugal force" is 170 W, the power consumption for

5

10

15

25

Figure 13B shows an example of the "search for

correspondence table" web page. When the user inputs the name of the manufacturer (for example, "Matsushita Electric Industrial Co., Ltd."), the type of the electric product (for example, "washing machine") and the item number or the model name of the electric product (for example, "XXXX") and clicks "search", a "confirm the correspondence table" web page is displayed on the screen of the terminal 420. The "confirm the correspondence table" web page allows the user to confirm the correspondence table specified by the name of the manufacturer, the type of the electric product, and the item number or the model name of the electric product input by the user.

Figure 13C is an example of the "confirm the correspondence table" web page. When the user clicks "download", the content of the "confirm the correspondence table" web page (i.e., the correspondence table specified by the name of the manufacturer, the type of the electric product, and the item number or the model name of the electric product input by the user) is downloaded to the terminal 420 from the server computer 410 through the internet 430. Such downloading is achieved by cooperation of the download programs installed in both of the server computer 410 and the terminal 420 beforehand.

When there is no need to confirm the search result of the correspondence table, the display of the "confirm the correspondence table" web page shown in Figure 13C can be omitted. In this case, the search result (i.e., the correspondence table specified by the name of the manufacturer, the type of the electric product, and the item number or the model name of the electric product input by the user) can be downloaded to the terminal 420 from the

server computer 410 through the internet 430.

5       The terminal 420 is connected to the power supply  
system 1 (Figure 1). The power control apparatus 30 in the  
power supply system 1 includes a memory (not shown) therein  
for storing a correspondence table. In this structure, the  
correspondence table downloaded from the server computer  
410 can be stored in the memory in the power control apparatus  
30. The power control apparatus 30 receives a state signal  
10       indicating a state (power state) of an electric product 40-1  
and converts the state into a power consumption of the  
electric product 40-1 in the state indicated by the state  
signal, using the correspondence table stored in the power  
control apparatus 30.

15       Alternatively, when the power control apparatus 30  
acts as a home server, the correspondence table can be  
downloaded from the server computer 410 to the power control  
apparatus 30 without via the terminal 420.

20       In this manner, the correspondence table downloaded  
from the server computer 410 can be used in the power control  
apparatus 30. Thus, in the case where an electric product  
connected to the power control apparatus 30 is replaced with  
25       another electric product or an electric product is  
additionally connected to the power control apparatus 30,  
the power supply system 1 can easily be conformed to the  
new environment of use without any work of the user.

30       When an electric product is sold to a user, a URL  
address for obtaining a correspondence table regarding the  
electric product can be attached to the electric product.  
For example, such a URL address can be described in the

warranty or service specifications (user's manual) packaged with the electric product. The user can easily obtain the correspondence table regarding the electric product purchased by accessing the web page designated by the URL address. Consequently, the user can easily add the electric product to the power supply system 1.

The terminal 420 can be connected to the power supply system 2 (Figure 3) or the power supply system 3 (Figure 6) instead of the power supply system 1 (Figure 1).

In the fourth example, the internet 430 is used. Any type of network is usable instead of or in combination with the internet 430.

According to the current invention, a second power request signal as a counting result of a plurality of first power request signals from a plurality of electric products is output to a power generation apparatus. An amount of power generated by the power generation apparatus is controlled by the second power request signal. By such a system, the power generation apparatus can be controlled to generate a "necessary amount" of power "when necessary" in response to a request from the electric products. As a result, the amount of power generated by the power generation apparatus is not unnecessarily increased, which achieves energy savings.

According to the current invention, in response to a matching signal, an acknowledging signal is output to each of at least one electric product which outputs a first power request signal among the plurality of electric products. The at least one electric product which outputs the first

5

25

30

[illegible]

appended hereto be limited to the description as set forth herein, but rather that the claims be broadly construed.

RECEIVED JUN 11 1960